TECHNICAL INFORMATION

PRODUCT : MPAT-CW

GLOSS PP OVERLAMINATING LABEL

PPCLTG20/PS-07/CKWHOM130

SURFACE		**PPCLTG20**
Type	**Polypropylene Film**	
PHYSICAL PROPERTIES		GENERAL CHARACTERISTIC
Thickness	0.020 ± 0.002 mm	1. Gloss clear polypropylene film
Basic weight	18 ± 2 gsm.	2. Water, moisture and chemical resistance

ADHESIVE		**PS-07**
Type	**Acrylic Solvent Base**	
PROPERTIES		GENERAL CHARACTERISTIC
Adhesion (S/Steel)	≥ 6.5 N/25 mm	1. Transparent adhesive
Loop tack	12.5 ± 2.2 N/25 mm	2. Good adhesion and suitable for
End user temperature	min. - 5°C max 70°C	metal, plastic, paper and glass etc.
Providing range	min. - 20 °C	
Shelf life	1 year under optimum storage condition	

LINER		**CKWHOM130**
Type	**Clay Coated Release Paper**	
PROPERTIES		
Basic Weight	130 ± 5 gm/m^2	
Thickness	0.130 ± 0.010 mm.	
Color	White	

APPLICATION

For laminate in applications where resistance against water, oil, and chemicals is important E.g. labeling toiletries, cosmetics and other print to protect from scratch and others.

CAUTION

1. All technical data statements are typical and should not be used for specification purpose.
2. The Product must be stored in shady (or cool) place and do not expose to sunlight directly.
3. Before using, user shall determine the suitability of the product for their intended use.

Note : 1. Peel adhesion and Loop tack value are measured by ASTM, FINAT and JIS test method ones under control condition (23 ± 2°C, 50 ± 5%) and not guaranteed.

2. Substrates to be applied and methods of application may be distinguishable. You may contact us for more details through Technical Development Staff at technical@thaikk.co.th or call number +662-338 4681-5

BY RESEARCH AND DEVELOPMENT (KK) SECTION (Revised: 2020)

© 2013 Thai KK Industry Co., Ltd All right reserved.

Thai KK Industry Company Limited.
Head Office 29/1 Moo.5 Soi Thummasiri, Debaratana Road, Tumbol Bangsaotong, Amphur Bangsaotong Samutprakan 10570 Thailand

Contact us
Tel : +662 338 4900
Fax : +662 338 4905