

TECHNICAL INFORMATION

PRODUCT : PL : WOOD FREE PAPER LABEL

WFWHOM70/PE-35/KRYEOM74

SURFACE **WFWHOM70**

Type	Matt White Wood free Paper	
<u>PHYSICAL PROPERTIES</u>		<u>GENERAL CHARACTERISTIC</u>
Basic weight	70 ± 5 g/m ²	1. Suitable for general print application.
Thickness	0.090 ± 0.005 mm	2. Application where matted white paper.

ADHESIVE **PE-35**

Type	Acrylic Emulsion	
<u>PROPERTIES</u>		<u>GENERAL CHARACTERISTIC</u>
Adhesion (S/Steel)	≥ 20 N/25mm	1. Permanent type which high Initial tack and high peel adhesion.
Loop Tack	17.0 ± 3.5 N/25mm	2. Good adhesion to metal, plastic, paper and glass etc.
End user temperature	min. - 5 °C max. + 80 °C	3. The adhesive complies with FDA 175.105 and approved for indirect contact food.
Providing range	min. -20 °C	4. Good for weather resistance.
Shelf life	1 year under optimum storage condition	

LINER **KRYEOM74**

Type	Kraft Release Paper	
<u>PROPERTIES</u>		
Basic Weight	87 ± 5 g/m ²	
Thickness	0.107 ± 0.010 mm	
Color	Yellow	

APPLICATION

For product labeling applications which suitable for all high quality label application.

CAUTION

1. All technical data mentioned in this technical data sheet are based on test performed in our laboratory with ASTM and FINAT testing method that control condition and should not be used for specification purpose and not guaranteed.
2. Before using, user shall determine the suitability of the product for their intended use.
3. The Product must be stored in shady (or cool) place and do not expose to sunlight directly.

Note : 1. Peel adhesion and Loop tack value are measured by ASTM, FINAT and JIS test method ones under control condition (23 ± 2°C, 50 ± 5%) and not guaranteed.

2. Substrates to be applied and methods of application may be distinguishable. You may contact us for more details through Technical Development Staff at technical@thaikk.co.th or call number +662 338 4681-5

BY RESEARCH AND DEVELOPMENT (KK) SECTION (Revised: 2019)

