

## TECHNICAL INFORMATION

**Product Code : RF7002**  
**Product Name : Polyester release film**

NO.	PHYSICAL PROPERTIES	UNIT	SPECIFICATION
1	Thickness	mm	0.030 ± 0.005
2	Basic weight	g/m <sup>2</sup>	40 ± 5
3	Tensile strength	Kg	MD ≥ 6 , CD ≥ 8
4	Release force	gf	6 ± 2
5	Color	-	Transparent

Application: Used as a high smooth, strength and clear released liner.  
 Shelf-life: 1 year under optimum condition.  
 Caution: 1. All technical data statements are typical and should not be used for specification purpose.  
 2. The Product must be stored in shady (or cool) place and do not expose to sunlight directly.  
 3. Before using, user shall determine the suitability of the product for their intended use.

*BY RESEARCH AND DEVELOPMENT (KK) SECTION (Revised: 2020)*

**Note :** 1. Release force and Silicone coating weight value are measured by FINAT test method ones under control condition (23 ± 2 °C, 50 ± 5%) and not guaranteed.

2. Adhesive coating and method of application may be distinguishable. You may contact us for more details through Technical Development Staff at [technical@thaikk.co.th](mailto:technical@thaikk.co.th) or call number +662-338 4680-5